

RS-RFT-002-2025
Request for Tender
DSMA Roof Replacement

Addendum No. 2
(to the Request for Tender Document)

The Request for Tender (RFT) is modified as set forth in this Addendum. The original RFT Documents and any previously issued addenda remain in full force and effect, except as modified by this Addendum, which is hereby made part of the RFT. Respondents shall take this Addendum into consideration when preparing and submitting its response.

1. Specification Change

The City has made one change to the proposed products for the project. The specifications changed are outlined below:

Appendix 01 Page 7 Section 2.04.2	
Remove:	SarnaTherm Roof Board A-III - Roof Type A & C A rigid isocyanurate foam insulation with glass facers. (SarnaTherm is available in 4 ft x 4 ft (1.2 m x 1.2 m) or 4 ft x 8 ft (1.2 m x 2.4 m) sizes. Consult Product Data Sheet for additional information. Compliance: CAN/CGSB-51.26-M86 CAN/ULC-S704 Insulation Type: 2 Class: 3 Board Dimensions: 1220 x 2440 mm (48 x 96 in.) Compressive Strength ASTM D1621: 550kPa (80.0 psi) nominal Thickness: 13 mm (0.5 inches)

Replaced With:	Dens Deck Primed - Roof Type A & C A siliconized gypsum, fire-tested utility board with glass-mat facers. Board Dimensions: 48 x 96 in. Compressive Strength ASTM C473: 900 psi Thickness: 1/4"
Appendix 01 Page 11 Section 3.05	
Remove:	Note: Roof Type A: install 0.5 inch rigid insulation as specified over existing dry and undamaged insulation Roof Type B: install 2 layers of 2.0" ridged insulation as specified Roof Type C: install 0.5 inch rigid insulation as specified
Replaced With:	Note: Roof Type A: install 1/4" gypsum utility board as specified over existing dry and undamaged insulation Roof Type B: install 2 layers of 2.0" ridged insulation as specified Roof Type C: install 1/4" gypsum utility board as specified



Mathew Bahm
 Director of Recreation

Issued: October 22, 2025

CITY OF TEMISKAMING SHORES
 P.O. Box 2050
 Haileybury, ON
 P0J 1K0